Motion detector - Professional Line

sensIQ S KNX

V3 white EAN 4007841 059613

























manufacturer's warranty steinel-professional.de/garantie

Function description

The evolution of perfection. The sensIQ S is just as perfect as its larger role model. For indoors and outdoors, ideal for building entrances, loading bays, for mounting heights of up to 5 m, quadruple sensor system for optimum surveillance over 3x100° coverage angle, 20 m reach (tangential), reach setting to the accuracy of a metre in 3 independent directions. Remote control and corner wall mount bracket included.

Technical specifications

Туре	Motion detectors
Dimensions (L x W x H)	128 x 114 x 74 mm
Sensor Technology	passive infrared
Application, place	Indoors, Outdoors
Installation site	wall, corner
Installation	Surface wiring
Mounting height	2 – 5,00 m
Reach, radial	$r = 4 \text{ m } (42 \text{ m}^2)$
Reach, tangential	$r = 20 \text{ m} (1047 \text{ m}^2)$
Reach, detail	Reach adjustable from 2 - 20 m in 3 directions (100° in each)
Detection angle	300 °
Angle of aperture	180 °
Optimum mounting height	2 m
Mechanical scalability	Yes
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No

Twilight setting TEACH	Yes
Twilight setting	2 – 1000 lx
Constant-lighting control	Yes
Basic light level function	Yes
KNX functions	Light output 2x, Presence output, Light level, Constant-lighting control, Basic light level function, Photo-cell controller, Close range, Individual pyro evaluation, Logic gate
Settings via	ETS software, Remote control, Bus, Smart Remote
With remote control	Yes
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Ambient temperature	-20 – 50 °C
Application, room	multi-storey / underground car park, outdoors, warehouse, front door, all round the building, courtyard & driveway, Indoors
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	white
PU1, EAN	4007841059613

Motion detector - Professional Line

sensIQ S KNX

V3 white EAN 4007841 059613




Accessories

EAN 4007841 608835

Corner wall mount sensIQ S

Detection Zone



Mögliche Montagehöhe: 2,00 m - 5,00 m

Orange: radial Schwarz: tangential 3 skalierbare Zonen

Dimension Drawing

