Motion detector

IS 360-1 DE

white EAN 4007841 032845











1000 W max.





2 - 2000 lux











manufacture's warranty steinel.de/garantie

CE

Function description

Intelligent technology for installation. Infrared wall sensor IS 360-1 DE, for indoors and out, ideal for installing in projecting roofs and suspended ceilings, 360° angle of coverage, reach can be set up to 4 m, selectable time and twilight threshold, detection zone can be customised with shrouds.

Technical specifications

Туре	Motion detectors
Dimensions (Ø x H)	78 x 89 mm
Mains power supply	230 – 240 V / 50 – 60 Hz
Sensor Technology	passive infrared
Application, place	Outdoors, Indoors
Application, place, room	outdoors, front door, all round the building, terrace / balcony, Indoors
Installation site	ceiling
Installation	Installation
Switching zones	306 switching zones
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,50 – 4,00 m
Optimum mounting height	2,5 m
Detection angle	360 °
Angle of aperture	90 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, radial	Ø 4 m (13 m²)
Reach, tangential	Ø 8 m (50 m²)

Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	8 s - 35 Min.
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs fluorescent lamps	[/] 6 pcs.
Constant-lighting control	No
Basic light level function	No
Settings via	Potentiometers
With remote control	No
Interconnection	Yes
IP-rating	IP54
Material	Plastic
Ambient temperature	-20 - 40 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	3 years
Version	white
PU1, EAN	4007841032845


Motion detector

IS 360-1 DE

white EAN 4007841 032845



Detection Zone



Mögliche Montagehöhe: 2,50 m - 4,00 m

Orange: radial Schwarz: tangential

Dimension Drawing

